

# Data sheet

SyrDos™ 10 ml XLP-Longlife-Syringe



## Product Description

The SyrDos™ 10 ml XLP-Longlife-Syringe is compatible with the SyrDos™ syringe pump XLP series and achieves a flow rate of 62.5 µl/min...62.5 ml/min in tandem operation mode. The carbon reinforced plunger increases the syringe life by up to 10 times.

- ✓ High-quality materials
- ✓ Large volume range
- ✓ 1/4"-28 UNF syringe head
- ✓ Seal included
- ✓ Increased endurance



Illustration similar

## Characteristics

Test pressure	16 bar
Nominal pressure (EN61010-1)	8 bar
Nominal pressure (2014/68/EU)	11 bar
Nominal volume	10 ml
Operating temperature	23...40 °C
Storage/cleaning temperature	-40...150 °C at 150 °C max. 15 minutes at 110 °C max. 60 minutes
Min. resolution	12.5 µl/min

## Dimensions

Inner diameter	14.14 mm
Outer diameter	17 mm
Length	60 mm
Weight	46 g

## Material/Connection

Wetting parts	PTFE/Carbon, borosilicate glass
Plunger material	PTFE/Carbon
Connection	1/4"-28 UNF

## Product Code

## Description

IP-SYR-XLP-BL-10000	Glass syringe, with carbon reinforced PTFE plunger, for SyrDos™ XLP series, volume 10 ml, set
---------------------	---



### Attention

Syringes are wearing parts. When used with abrasive media, it leads to increased wear!

HiTec Zang GmbH  
Ebertstraße 28-32  
52134 Herzogenrath  
Germany  
+49 (0)2407 / 910 100  
info@hitec-zang.de  
www.hitec-zang.de

